Namiti S.r.l. - P. Iva 06162571217 - N. Rea: 799272
Sede leg.: Via Cortile, 16 - 80069 Vico Equense (NA)
Sede Op.: Corso Italia, 192 - 80063 Piano di Sorrento (NA)
Email: vendite@holity.com / Tel. 0818087452



Aluminum loading ramp with edges h1026_03

Non-slip aluminum ramp with side edges. Length: 199.1 cm. Profile height: 6.5 cm. Capacity: 1000 kg.

The **aluminum loading ramp H1026_03** with **safety side edges** is designed for daily **loading and unloading** operations in professional environments. Its **non-slip tread surface** makes it ideal for use with **manual pallet trucks, hand trolleys** and equipment equipped with **small rubber wheels**.

With a **length of 1991 mm**, an **external width of 750 mm** and an **edge height of 29 mm**, this ramp is designed to offer **maximum safety** and stability during use, preventing accidental lateral slippage thanks to the presence of **protective edges**. The **capacity of 1000 kg at 1000 mm wheelbase** makes it perfect for logistics contexts, transport companies, trade fairs and events.

It is equipped with an **aluminum tongue anchoring system**, which can **slide across the width and rotate** in the head, easily adapting to different loading surfaces. **Head closing caps** are supplied to prevent accidental exit of the tongue, thus ensuring **greater safety during the operational phase**.

The **lightweight aluminum structure**, combined with the robustness and efficiency of the ramp, makes it a **reliable and durable solution** for those looking for practicality and safety in daily work.

Order the **H1026_03 ramp now!** Aluminum ramp with side edges and secure anchoring, ideal for logistics activities, transport and setups.

Technical features:

- **Material:** aluminum
- **Type:** loading ramp with side edges
- **Tread surface:** non-slip
- **Standard length (L):** 1991 mm
- **Internal width (A):** 690 mm
- **External width (B):** 750 mm
- **Edge height (C):** 29 mm
- **Profile height (D):** 65 mm
- **Overall dimensions with edges (E):** 83 mm
- **Capacity:** 1000 kg at 1000 mm wheelbase
- **Unit weight:** 24 kg
- **Anchoring system:** mobile aluminum tongue
- **Equipment included:** head closing caps

Benefits for the user:

- **Safety:** increased thanks to anti-slip side edges.
- **Surface:** non-slip for operations in total stability.
- **System:** adjustable and secure anchoring system with aluminum tongue.
- **Aluminum structure:** lightweight but highly resistant.
- **Ideal:** for logistics, transport, events and goods handling.

FAQ:

1. **Is this ramp suitable for use with manual pallet trucks?**
   Yes, it was designed specifically for manual pallet trucks and trolleys with rubber wheels.
2. **Does it have edges?**
   Yes, this version is equipped with edges.
3. **How does the anchoring system work?**
   The aluminum tongue slides and rotates in the ramp head for stable and adaptable fastening.
4. **What capacity does it support?**
   It can support up to 1000 kg at 1000 mm wheelbase, perfect for heavy-duty use.
5. **What is its length?**
   Its length is 199.1 cm.

Mini purchase guide:

If you work in the **logistics, transport, beverage distribution, events or trade fairs** sector, an **aluminum ramp with edges** like the **H1026_03** is the ideal solution.

Thanks to the **non-slip structure**, **high capacity** and **containment edges**, it is perfect for frequent manual loads.

The mobile anchoring tongue ensures simple and stable fastening.

Choose it if you are looking for a **solid, safe, versatile and durable ramp** for professional use.

Loading ramp with edges H1026_03, aluminum ramp for pallet trucks, logistics ramp with non-slip surface, ramp for manual trolleys with anchoring, aluminum loading and unloading platform with edges.

**Images purely indicative.*

INFORMATION

- **Load capacity** 1000 Kg
- **Side edges** With edges

Aluminum loading ramp with edges h1026_03





Aluminum loading ramp with edges h1026_03

Flow rate: 1000 Kg
Side edges: With edges

