



Cast iron gully grate with square frame h638_151

Spheroidal cast iron gully grate with square cover. Class: C250. External dimensions: 450 x 450 mm.

This **spheroidal cast iron gully grate** made according to the latest edition of the **UNI EN 124** standard, is ideal for parking areas, side gutters and paving with interlocking blocks. Produced by an **ISO 9001:2015** certified company, this gully grate is designed to guarantee quality and safety. Its structure is composed of a **frame, without an external perimeter flange, of square shape** both at the base and at the top, aligned with the level of the road surface. The product is equipped with a **square grid** provided with **parallel slots** arranged in two rows; **central concavity of 8 mm** to favor the useful slope on the extrados; central space for **any inscriptions**; and **non-slip reliefs** to guarantee the safety of users.

Technical features:

- External dimensions: 450 x 450 mm
- Height: 80 mm
- Clear opening: 400 x 400 mm
- Drainage: 6 dm²
- Total weight: 29 kg
- Material: spheroidal cast iron
- Frame shape: square
- Frame without external perimeter flange
- Cover shape: square
- Class: C250
- Made according to the UNI EN 124 standard
- ISO 9001:2015 certification
- Breaking load > 250 kN
- Detail identifying the external dimensions of the frame expressed in cm
- Space for possible customization
- Grate with high drainage capacity

**Images purely indicative*

INFORMATION

- Length in millimetres 450.000000
- Depth in millimetres 450.000000
- Height in millimetres 80.000000

