



Convertible trolley with 2 puncture-proof wheels and 2 solid wheels h55_97

Convertible trolley in welded steel, 3 operating positions, capacity up to 400 kg. Ideal for logistics and HoReCa. Dimensions 560x550x1250 mm.

This **convertible crate trolley** represents a versatile and robust solution for manual load handling in multiple professional contexts. Thanks to a quick adjustment system that can be operated with one hand, the operator can choose between **three different configurations**: vertical with 2 wheels for standard loads, tilted with 4 wheels for greater transport stability, and platform with 4 wheels for bulky items. The **welded steel** structure, finished with epoxy powder coating in **green RAL 6018**, guarantees high mechanical resistance and protection against corrosion, making it suitable for intensive use in warehouses, laboratories, and hospitality facilities.

Technical features

- **Total dimensions:** W. 560 x D. 550 x h. 1250 mm
- **Operating weight:** approx. 21 kg
- **Load plate dimensions:** 420 x 220 mm
- **Capacity 2-wheel configuration:** 300 kg
- **Capacity 4-wheel configuration:** 400 kg
- **Material:** welded steel with epoxy powder finish
- **Color:** green RAL 6018
- **Main wheel system:** 2 puncture-proof PU wheels, steel rim Ø 260 mm
- **Auxiliary wheel system:** 2 swivel solid rubber wheels Ø 125 mm
- **Ergonomics:** non-toxic rubber grips with anatomical handle
- **Delivery:** product supplied fully assembled
- **Compliance:** CE certification

Image for illustrative purposes only

INFORMATION

- **Width in millimetres** 560.000000
- **Depth in millimetres** 550.000000
- **Height in millimetres** 1250.000000
- **capacity** 400 kg
- **Wheels** ruote piene
- **typology** pala

Convertible trolley with 2 puncture-proof wheels and 2 solid wheels h55_97



Convertible trolley with
2 puncture-proof wheels
and 2 solid
wheels h55_97

Capacity: 400 kg
Typology: pala
Wheels: ruote piene