



## Conveyor toaster 3 slices h23\_59

Professional ultra-fast conveyor toaster. External dimensions: W. 47 x D. 41 x h. 47 cm. Power supply voltage: 230 V 50-60 Hz.

Offering a breakfast buffet with toasted bread can make a customer pleasantly satisfied with their stay within a facility. The **professional toaster** is, in fact, **suitable for both buffet rooms and fast food, catering activities, pubs, burger shops.**

Thanks to the **heating speed** and its **durability**, this model is perfect for **heavy and continuous use** and for very intense work cycles 7 days a week, **even in environments where climatic conditions reach up to 35 °C.** Equipped with **quartz heating elements, separate power controls (top and bottom), stainless steel conveyor belt** adjustable in different speeds and **stainless steel crumb tray.** The belt allows for toasting a large quantity of products, adjusting the degree of toasting through the power controls, in a short time. This **rotary toaster** is also **insensitive to the texture of the bread**, managing to toast and heat slices of different thicknesses simultaneously, slices up to 6 cm thick but also irregular, frozen and pre-cut bread slices.

**Quality, durability and flexibility** are the key words for a toaster totally **Made in Italy.**

### Technical features:

- Production/h: +950 slices
- Toasting chamber dimensions: 37 x 6 cm
- External dimensions: W. 47 x D. 41 x h. 47 cm
- Absorbed power: 3.4 Kw
- Weight: 31 kg
- Power supply voltage: 230 V 50-60 Hz
- Cable length: 2.5 m Schuko
- Quartz heating elements
- Separate power controls, top and bottom
- Stainless steel conveyor belt with adjustable speed
- Stainless steel excess crumb collection tray
- Resistant to environments with temperatures up to 35 °C
- Designed for constant use
- Insensitive to bread texture
- Increased chamber dimensions for toasting bread slices up to 14 x 14 x h. 6 cm
- Quick-release panel fastening system for immediate access to the internal parts of the machine
- Enhanced belt drive system with anti-slip technology in the presence of oil
- Removable and replaceable filter for the protection of internal components
- Resettable safety thermostat that intervenes before components and the electrical board can break
- Resettable safety thermostat on the panel
- Quick heating element replacement system
- Quick disassembly of the rear chute
- CE certification

*\*Images for illustrative purposes only.*

- **tipologia** a nastro
- **produzione oraria** 950 fette