



Digital operating room clock h775_09

Operating room clock with keyboard. Afnor movement. Dimensions: W.420 x D.45 x H.130 mm.

Professional operating room clock with sanitizable stainless steel case and protective glass. The item works via **Afnor technology with intelligent code transmission** and requires a master clock to drive it through the relative output pulses, available upon request for a quote. The display of hours, minutes, seconds or stopwatch via numerical characters with a height of **5 cm with red LEDs**.

Clock technical features:

- Red LED digital clock
- Stainless steel casing (IP65, IK07) with mineral glass protection and keyboard compliant with operating room requirements.
- For indoor use
- Display of hours, minutes and seconds
- Character height: 5 cm
- Optimal reading distance: 20 meters
- AFNOR movement operation
- Recessed mounting with 4 holes
- Reading angle: 120°
- Silent operation
- Programming and setting via 2 buttons
- Digits consisting of 7 segments with 3 LEDs each
- Consumption: 55mA
- Operating temperature: from -5 to 55°C
- Weight: approx. 1.2 kg
- Electrical protection: class 2
- Dimensions: W.420 x D.45 x H.130 mm

Keyboard technical features:

- Stopwatch hours - minutes - seconds from 0 to 23:59:59
- Waterproof with touch-sensitive keys
- Time display key with LED indicator.
- Stopwatch function key with LED indicator.
- Start/Stop key.
- Reset key: resets the stopwatch to zero.
- Connection to the clock via 2-wire telephone cable; maximum length 20 meters.
- Power supply via clock.
- Ability to manage up to 10 clocks.
- Operating temperature: from 0 to 50°C
- Protection rating: IP55
- Weight: 255g

Separately, as an **option**, it is possible to purchase the **recessed version of the keyboard** and the **back cover**, useful for protecting the clock from dust and humidity.

**Other LED colors are available upon request for a quote*

*** This clock requires a master clock to drive it through the relative output pulses, available upon request for a quote*

INFORMATION

