



Double cylinder trolley with puncture-proof wheels and handle h55_118

Double steel trolley for 40/50 l cylinders. Puncture-proof wheels, electro-welded structure and safety chains for industrial and medical use.

The **double cylinder trolley** is a professional solution designed for the safe and assisted handling of **two 40/50 litre cylinders** with a diameter of 230 mm. Ideal for contexts requiring the movement of heavy loads on irregular surfaces, this tool solves the critical issues related to stability and operator fatigue, finding optimal use in both **industrial** and **hospital** settings. The structure is entirely made of **electro-welded steel** with laser-cut loading plate (thickness 30/10), ensuring superior structural strength and long operational life.

Technical characteristics

- **Capacity:** Housing for 2 cylinders of 40/50 litres (Ø 230 mm)
- **Standard dimensions:** L. 810 x D. 490 x h. 1335 mm
- **Transport configuration dimensions:** L. 810 x D. 1210 x h. 1000 mm
- **Maximum capacity:** 200 kg
- **Net weight:** approx. 24 kg
- **Material:** Electro-welded steel with oven-dried epoxy powder coating
- **Wheel system:** 2 main puncture-proof wheels Ø 300 mm and 2 swivel solid rubber wheels on joint Ø 125 mm
- **Mechanics:** Rolling on roller bearings; maximum speed of use 4 km/h
- **Safety:** Containment system with high-visibility red painted chain
- **Included accessories:** Tool box (475 x 155 x h. 170 mm) and ergonomic handle
- **Compliance:** CE certification

Image purely indicative

INFORMATION

- **Capacity** 40/50 lt

Double cylinder trolley with puncture-proof wheels and handle h55_118



Double cylinder trolley
with puncture-proof wheels
and handle h55_118

Capacity: 40/50 lt