



Ductile iron road manhole cover h638_27

Ductile iron manhole cover. Dimensions: 500 x 500 x H.85 mm. Clear opening: Ø 400 mm.

Ductile iron manhole cover with a square frame at the base and a circular top, ideal for covering aqueducts, sewers, or inspection chambers on roads and pedestrian areas. **The product is essential for leveling the road surface and ensuring safety**, preventing dangerous openings in the ground. **The anti-slip reliefs on the cover ensure water runoff**, while the “U”-shaped internal seat with elastomer gasket **reduces noise and oscillation**.

Technical features:

- Adequate continuous external perimeter flange equipped with slots for better anchoring in the foundation
- Lifting eyes for handling during installation
- Closed-bottom hinge compartment with lid locking system in the open position
- Closed-bottom slot suitable for the opening and lifting key
- Steel locking system made by a bolted rotating latch with a helical return spring
- Appendix suitable for ensuring the lid-to-frame articulation in the hinge compartment without preventing the removal of the lid itself
- External dimensions: 500×500 mm
- Clear opening: Ø 400 mm
- Height: 85 mm
- Weight: 29 kg
- Frame shape: square
- Cover shape: circular
- Hinge: 110° Max hinge, 90° block hinge, Key, Gasket

INFORMATION

- **Material manhole covers** ghisa
- **manhole_dimensions** 500 x 500 mm

Ductile iron road manhole cover h638_27

Ductile iron road manhole cover h638_27

Manhole cover dimensions: 500 x 500 mm

Manhole cover material: ghisa

