



Electric bed for hospital rooms h937_17

Electric hospital furnishing bed. 3 joints and 4 sections. Dimensions: L. 214 x W. 101 x h. 35 - 75.5 cm.

Hospital bed for clinics and care homes designed to ensure optimal comfort and functionality for both the patient and the healthcare provider. Equipped with **three joints and four sections**, it offers **total electric movement** with **variable bed base height** via **two independent electric motors**. The **bed base structure**, measuring **90x200 cm**, is made of **steel** with **movable sections in oval-section tubing**, while the **bed base** consists of **steel slats** with **integrated mattress retainer guides**. The **headrest section** and the **leg section** are **electrically adjustable** via **handset**, while the **foot section** is **rack-adjustable** and the **pelvis section** remains **fixed**. The bed is equipped with **supports for the patient lifter pole** and **for the IV pole**, as well as **vertical sliding side rails**, made of **wood with a natural beech finish**, with upper and lower lock/unlock buttons for lowering and removing the rails. The **head and footboards** of the bed have a **painted steel internal structure, clad in wood with a beech finish**. The **legs**, integrated into the head and footboards, are equipped with **four 125 mm swivel castors**, each with an **independent brake**. The **Trendelenburg** movement up to **12°** and **anti-Trendelenburg** up to **-12°** is managed via handset. The **finish** of the bed is in **grey epoxy paint** applied to a sandblasted surface, ensuring strength and durability. The bed is supplied with a patient lifter pole complete with triangle and adjustable nylon strap.

Technical features:

- Total external length: 214 cm
- Total external width: 101 cm
- Maximum patient weight: 135 kg
- Safe working load: 170 kg
- Total weight: 92 kg
- Internal length (base): 200 cm
- Internal width (base): 88 cm
- Base/ground height: 35 - 75.5 cm
- Headboard height: 51 cm
- Wheel diameter: 10.5 cm
- Actuator nominal voltage: 24 V
- Power supply voltage: 230 V, 50Hz
- Active power consumption: 100 W
- Intermittent operation: 2-18
- Insulation class: Class II
- Protection degree: IP 54
- 3 joints, 4 sections
- Total electric movement
- 90x200 cm bed base
- Variable bed base height via two independent electric motors
- Bed base frame in rectangular section steel profiles, movable sections in oval section steel tubing
- Bed base in steel slats with non-removable mattress retainer guides
- Headrest and leg sections electrically adjustable via 24V DC motors and handset
- Rack-adjustable foot section
- Fixed pelvis section
- Head and footboards with painted steel internal structure, single-block wood cladding with natural beech finish and solid wood edges
- Built-in sliding guides for inserting side rails
- Legs integrated into the head and footboards
- 4 swivel wheels Ø 125 mm, equipped with independent brake
- Trendelenburg movement up to 12° and anti-Trendelenburg up to -12°, controllable by handset
- Vertical sliding side rails with natural beech finish, fixed with sliding devices
- Upper and lower lock/unlock buttons for lowering and removing side rails
- Epoxy painting on sandblasted surface, grey colour
- Equipment: patient lifter pole with triangle and adjustable nylon strap

**Image for illustrative purposes only.*

INFORMATION

- **typology** elettrico
- **Wheels** Si
- **Length in millimetres** 2140.000000
- **Depth in millimetres** 1010.000000



Electric bed for hospital rooms h937_17



Electric bed for
hospital rooms h937_17

Typology: elettrico
Wheels: Si