



Flood barrier h729_62

Modular flood barrier made of tubular elements (2mm thickness). Useful height 60 cm, adjustable width 75-120 cm. Installation in only 5 minutes.

The **h729_62 modular flood barrier** is a passive protection device designed to secure homes, commercial premises and professional spaces against damage caused by floods and heavy rainfall. Aimed at private individuals, shopkeepers and facility managers, this floodgate solves the urgency of blocking water entry through doors and openings in extremely fast times. Thanks to the adjustable width from 75 to 120 cm and the useful height of 60 cm, it flexibly adapts to different types of entrances. The system requires an initial pre-installation of 3 hours to prepare the fixings, after which the barrier can be assembled and removed in just 5 minutes during emergency situations, ensuring optimal sealing through the use of a closed-cell foam gasket.

Technical characteristics


- **Type:** Modular flood barrier, adjustable and removable
- **Structure material:** Rectangular tubulars 60 × 30 mm, 45 × 25 mm and 40 × 20 mm (2 mm thickness)
- **Overall height:** 71.5 cm
- **Useful protection height:** 60 cm
- **Width:** Adjustable from 75 to 120 cm
- **Weight:** 27 kg
- **Sealing system:** Closed-cell foam gasket
- **Operating times:** Pre-installation time 3 hours; emergency installation time 5 minutes
- **Equipment included:** Sealant glue cartridge, screws for assembly and fixing of the panels (plastic wall plugs with coach screws)
- **Items not included:** Extruder gun for sealant glue not provided

** Images purely indicative*

INFORMATION

- **Length** 75 - 120 cm

Flood barrier h729_62



Flood barrier h729_62

Length: 75 - 120 cm