



Folding blood sampling chair 2 wheels h1016_07

Folding blood sampling chair with footrest, 2 wheels with brake and adjustable headrest. Steel structure and fire-retardant vinyl upholstery.

The **blood sampling chair with 2 wheels h1016_07** is designed to offer a perfect balance between **functionality, comfort and safety** during sampling and other medical procedures.

Made with a 30 mm diameter, 1.5 mm thick **round steel structure**, coated with **epoxy paint**, it guarantees strength and durability. The **backrest and leg rest**, independent and **folding** via 400N gas pistons, allow the patient's position to be adjusted according to needs.

The **seat padded with high-density polyurethane foam** ensures comfort, while the **height-adjustable padded armrests**, with a **chrome finish** and **black polyethylene coating**, increase support and practicality.

The **retractable footrest** and **adjustable headrest** complete an ergonomic and versatile structure. The **2 wheels with brake** allow easy movement and safe positioning.

The **technical vinyl fabric** upholstery is **antimicrobial, antibacterial, antifungal, antistatic, fire-retardant** and **resistant to urine and blood**, ensuring hygiene and safety in healthcare settings.

Choose the h1016_07 folding chair to offer comfort to patients and practicality to healthcare staff.

Technical features:

- **Structure:** Ø 30 mm round steel, 1.5 mm thickness
- **Finish:** epoxy paint
- **Handle:** to facilitate the chair's mobility
- **Backrest and leg rest:** folding, with independent 400N gas pistons
- **Seat:** padded in 30 kg polyurethane foam
- **Backrest and leg rest:** padded in 25 kg polyurethane foam
- **Internal structure:** in MDF
- **Upholstery:** antimicrobial, antibacterial, antifungal, fire-retardant, antistatic technical vinyl
- **Armrests:** chromed, height-adjustable, padded, coated in black polyethylene
- **Wheels:** 2 synthetic 125 mm wheels with brakes
- **Footrest:** retractable
- **Headrest:** adjustable
- **Total height:** 1120 mm

- **Total width:** 670 mm
- **Total depth:** 780 mm
- **Seat height:** 450 mm
- **Length in lying position:** 1650 mm
- **Useful seat:** 540x520 mm
- **Maximum patient weight:** 150 kg
- **Certification:** CE
- **Standards:** UNE-EN-ISO 14971:2020, UNE-EN-ISO 13485:2018, UNE-EN-ISO 16139:2013, UNE-EN-ISO 12182:2012

User benefits:

- **Independent adjustments:** folding backrest and leg rest with gas pistons.
- **Personalized comfort:** padded seat and adjustable headrest.
- **Practicality of use:** retractable footrest and height-adjustable armrests.
- **Safe mobility:** 2 wheels with brake for movement and stability.
- **Guaranteed hygiene:** technical antimicrobial and antibacterial upholstery.

FAQ:

1. Is the chair foldable?

Yes, both the backrest and the leg rest are foldable via gas pistons.

2. Is it suitable for patients needing extra support?

Yes, thanks to the adjustable armrests and headrest, it offers comfortable and safe support.

3. Do the wheels have a locking system?

Yes, both wheels are equipped with a brake to ensure stability during use.

4. Is the upholstery easy to sanitize?

Yes, the technical vinyl fabric is resistant and designed to ensure maximum hygiene.

5. In which contexts is it recommended?

It is ideal for hospitals, clinics and nursing homes, both for blood sampling and patient care.

Mini buyer's guide:

The **h1016_07 folding blood sampling chair** combines **mobility, comfort and safety**: equipped with **adjustable backrest and leg rest, retractable footrest** and **wheels with brake**, it meets the needs of modern healthcare facilities. The technical upholstery ensures hygiene and resistance, making it a reliable and durable choice.

Folding blood sampling chair, medical chair with wheels, clinic chair with footrest, adjustable hospital chair, folding medical chair with brake

**Images for illustrative purposes only.*

INFORMATION

- **flow rate** 150 kg
- **Operation** mechanic
- **type height** fixed



HOLITY.COM



HOLITY.COM

Folding blood sampling chair 2 wheels h1016_07

Flow rate: 150 kg
Operation: mechanic
Type height: fixed