



Gasoline transport tank 330 L h1042_11

Gasoline transport tank 330 L h1042_11 in black conductive LLDPE polyethylene, ADR approved (BAM 15862-CEMO6/0/407). Supplied assembled with internal baffle, gas spring lid and 12V pump.

The **Gasoline transport tank 330 L h1042_11** is a 330-liter mobile station approved for the road transport of highly flammable liquids, complying with strict ADR regulations (ADR Approval: BAM 15862-CEMO6/0/407). Made with a robust single-layer tank in high-quality uncoated black polyethylene (PE / LLDPE), the material features electrically conductive properties to prevent the accumulation of electrostatic charges. To ensure maximum safety during logistical operations, the structure integrates an internal baffle to reduce the sloshing and movement of the liquid during transit, a flame arrester device, and a filling neck with integrated ventilation and venting. The tank is topped by an orange flip-up lid assisted by a gas spring for easy opening and additional protection of the components. The body is also equipped with a mechanical level indicator, a nozzle holder to maintain order and cleanliness, ergonomic handles, forklift pockets, and structural recesses for secure fastening with ratchet straps. Supplied in fully assembled condition, this model is subject to mandatory periodic inspection every 2 and a half years according to ADR points 6.5.4.4.1 b) and ADR 6.5.4.4.2 b). The transfer system consists of a 12V DC electric pump with a maximum flow rate of 25 l/min, a 4-meter delivery hose (DN 19), an automatic gasoline nozzle, and a 5-meter long electric cable equipped with battery pole clamps.

Technical features

- **Capacity:** 330 l
- **External dimensions (L x W x H):** 118 x 79 x 57 cm
- **Weight:** 42 kg
- **Use:** mobile
- **Place of use:** transport
- **Material:** LLDPE (high quality polyethylene)
- **Coating:** uncoated
- **Material properties:** electrically conductive
- **Active safety devices:** integrated internal anti-slosh baffle and flame arrester device
- **Tank color:** black
- **Lid color:** orange
- **Lid:** yes (flip-up with gas spring)
- **Level indicator:** mechanical
- **ADR approval:** BAM 15862-CEMO6/0/407
- **Regulatory inspections:** mandatory periodic inspection every 2 and a half years according to ADR 6.5.4.4.1 b) and ADR 6.5.4.4.2 b)
- **Operating voltage:** 12V DC
- **Pump drive:** electric pump
- **Maximum flow rate:** 25 l/min max.
- **Delivery hose length:** 4 m
- **Hose diameter:** DN 19
- **Stackable:** no
- **Forklift pockets:** yes
- **Nozzle:** automatic for gasoline
- **Cable length:** 5 m

- **Plug / connection:** battery pole clamps
- **Compatible fluids:** Gasoline
- **Assembly status:** assembled
- **Warranty in years:** 1

** Images are purely indicative*

INFORMATION

- **Adatto per** Fuel
- **Capacità** 330 L



Gasoline transport tank
330 L h1042_11

: Fuel
: 330 L