





# **Bollard delimitation of urban areas h14033**

Bollard to delimit areas of urban design in galvanized steel. Above-ground height 100 cm, diameter 8.9 cm. Available with or without rings

Bollard ideal for defining urban areas, or private condominionali made with the best materials and Italian production. you can also use as a limiter to stop or parking lot.

## Structure:

- bollard made of tubular galvanized steel mm. ? 89 x 2 adorned with a frieze in the superioreda
- Decorative flange to cover the hole for the underground installation.

#### Anti-corrosion treatments and finishing:

#### Pre-treatment:

 before being painted, the building is pre-treated by a spray washing with special degreasing. After washing, the piece to be painted, is dried for 15 minutiin dryer.

## Anticorrosive treatment or:

• in order to impart suitable protection against atmospheric agents, the article is subjected to a first coating cycle using an anticorrosive primer in thermosetting powder epoxy diresine with special pigments.

Before kitchen (anticorrosive):

• the manufactured article treated with the anticorrosive primer is subjected to a first baking of duratadi 15 minutes at a temperature of 180 °. In this phase the anticorrosive polymerizes, forming a coating thickness of about 60 microns

#### **Painting**

• , the product was subjected to a final cycle of thermosetting powder coating with polyester resin-based color "gun barrel". The coating is performed with equipment spruzzoelettrostatico, that allow the powder to settle evenly on the pieces, forming a minimum thickness of 60 microns.

#### Glaze firing

• the coated manufacture is subjected to a final baking in the oven for a period of 20 minutes at a temperature of 160 °.

#### Fixing:

• through extension of the bollard in the subsurface.

#### Size:

- cm height above ground. 100
- in-ground cm. 20
- weight kg. 6.70

The card images may not faithfully reproduce the actual colors of the items.

# **INFORMATION**

- materiale\_dissuasori acciaio
- reflective band no
- Diametro 175.0000
- fixing da inghisare
- Tipologia Senza anelli
- Altezza in millimetri 1000.0000