



Sensor operated automatic hand dryer h4019

Small and compact automatic hand dryer with brush motor and propeller fan. Available in white abs

General Description

- Warm air hand dryer
- Sensor operated by hand approximation
- Suitable for medium traffic facilities
- Compact, small size
- Highest durability in its class
- It normally goes along with a soap dispenser.

Components and Materials

- White ABS thermoplastic one-piece cover, 3 mm thick. Cover fixed to the base by means of 2 metal sheet screws
- Thermoplastic PP + talcum base, with 4 Ø 6 mm holes for wall mounting (screws and wall plugs are provided)
- Universal brush motor, 15.000 rpm, class B, includes a self-resetable thermal cut-off at 100 °C
- PP UL94-V0 helicoidal fan wheel
- Waved Ni-Cr wire heating element that incorporates a self-resetable thermal cut-off at 95 °C
- Adjustable (5-20 cm) IR electronic detection sensor.
- IR Sensor with PC viewing screen

Technical Specifications

- Frequency 50/60 Hz
- Dimensions 258x 145x 138 mm
- Air velocity 85 Km/h
- Noise level (at 2 m) 60 dB
- Protection level IP23

INFORMATION

- **activation** photocell
- **Punti di forza** i meno rumorosi
- **tipologia** tradizionali
- **Material** plastica
- **warranty** 2 anni
- **Power** 950 W
- **Potenza in watt** 950.0000
- **Height** 25,8 cm
- **Profondità in millimetri** 138.0000
- **Larghezza in millimetri** 145.0000
- **Altezza in millimetri** 258.0000
- **Depth** 13,8 cm
- **Width** 14,5 cm
- **Tempo di asciugatura** 45 sec
- **Color** bianco