



Hermetic road manhole cover 50x70 cm h638_90

Ductile iron manhole cover. Class C250. Dimensions: 500x700 mm

Ductile iron manhole cover, produced according to the latest edition of the **UNI EN 124 standard, load class C250**, for use in car parks, yards, industrial sites and areas with slow-moving traffic. By an **ISO 9001:2015 certified company**, consisting of a **rectangular** frame at both the base and the top corresponding to the road level, equipped with a suitable outer perimeter flange, continuous on all four sides to obtain a larger base and allow better anchoring to the foundation; internal "U" seat to achieve odor-tightness by filling with sand and/or equivalent materials in conjunction with the cover; rounded internal corner for unique insertion of the cover. Rectangular cover equipped with closed-bottom slot(s) suitable for receiving lifting keys; space for the insertion of any lettering and/or logos (e.g. contracting authority + etc.); rounded corner for unique insertion into the frame; anti-slip patterns uniformly distributed for complete drainage of surface water.

Technical features:

- Material: ductile iron
- External dimensions: 500x700 mm
- Clear opening: 400x600 mm
- Height: 45 mm
- Hermetic
- Frame shape: rectangular
- Cover shape: rectangular
- Class: C250
- Weight: approx. 31 kg

*image for illustrative purposes only

INFORMATION

- **Material manhole covers** ghisa
- **manhole_dimensions** 500 x 700 mm



Hermetic road manhole cover 50x70 cm h638_90

Manhole cover dimensions: 500 x 700 mm

Manhole cover material: ghisa