



Inclusive carousel h350_352

Inclusive carousel for 6 users. Maximum overall dimensions: Ø 240 x h. 83 cm. EN 1176 certified.

Inclusive carousel ideal for playgrounds and outdoor play areas. The **supporting structure** is made of **galvanized steel** sec. 5x3 cm. The carousel includes **1 platform** in phenol-bonded birch plywood with non-slip knurling, finished with colored films; **4 railings** in steel tube that define the users' waiting area; **1 central handlebar** in phenol-bonded birch plywood finished with colored films. The carousel is complete with **standard-compliant devices for locking wheelchairs**. The rotation of the structure occurs via **load-bearing roller bearings**. The **assembly bolts** are in **8.8 galvanized steel** and **self-locking nuts**, covered by standard-compliant **nut caps** in colored nylon. The **maximum number of users** is **6** and the equipment is **suitable for children from 2 to 16 years old**. The product is **EN 1176 certified**.

Technical characteristics:

- Inclusive equipment
- Maximum overall dimensions: Ø 240 x h. 83 cm
- Supporting structure material: galvanized steel tubular sec. 5x3 cm
- Age of use: 2-16 years old
- Number of users: 6
- Fall height: 41 cm
- Impact area: 35 sqm
- Minimum space: 650 x 650 cm
- 1 platform in phenol-bonded birch plywood with non-slip knurling
- Platform finishing with colored films
- 4 railings in Ø 40 mm steel tube, oven-painted at 180°
- 1 central handlebar in phenol-bonded birch plywood
- Central handlebar finishing with colored films
- Standard-compliant devices for locking inclusive wheelchairs
- 8.8 galvanized steel bolts
- Self-locking nuts
- Nut caps in standard-compliant colored nylon
- EN 1176 certified

**Images for illustrative purposes only.*

INFORMATION

- places 6
- Diameter 2400.000000
- Height in millimeters 830.000000