Namiti S.r.l. - P. Iva 06162571217 - N. Rea: 799272
Sede leg.: Via Corile, 16 - 80069 Vico Equense (NA)
Sede Op.: Corso Italia, 192 - 80063 Piano di Sorrento (NA)
Email: vendite@holity.com / Tel. 0818087452



Loading ramp with edges h1026_01

Non-slip platform for carts and pallet trucks. Length: 179.1 cm. Upright height: 6.5 cm. Capacity: 1000 kg.

The **H1026_01 loading ramp with edges** is designed to facilitate **loading and unloading operations** in total safety within industrial, logistics, and exhibition contexts. Equipped with a **special non-slip surface**, it is particularly suitable for use with **manual pallet trucks, hand trucks**, and other **equipment with rubber wheels**.

Built to ensure **maximum strength and stability**, this ramp has a **capacity of 1000 kg at a 1000 mm wheelbase**, making it perfect for high-load activities such as **beverage delivery, goods handling, removals, events**, and general logistics.

The structure includes **safety side edges** to prevent accidental run-offs during the passage of equipment. It is also equipped with **aluminum anchoring tongues**, designed to slide along the width and rotate in the head of the ramp. This flexibility allows for **secure and versatile anchoring** to the support surface. To complete the system, **head closure caps** are included, preventing the tongue from slipping out during use.

The H1026_01 is a **robust and practical solution** for every handling need in professional environments.

Buy the **H1026_01 loading ramp now!** Contact us for personalized quotes, corporate supplies, or custom versions with/without edges.

Technical specifications:

- **Type:** ramp with safety side edges
- **Surface:** special non-slip floor
- **Tongue material:** aluminum
- **Capacity:** 1000 kg at 1000 mm wheelbase
- **Standard length (L):** 1791 mm
- **Internal width (A):** 690 mm
- **External width (B):** 750 mm
- **Edge height (C):** 29 mm
- **Upright height (D):** 65 mm
- **Overall dimensions with edges (E):** 83 mm
- **Unit weight:** 21 kg
- **Standard equipment:** movable anchoring tongues + head closure caps

User benefits:

- **Maximum:** safety thanks to the side edges.
- **Surface:** non-slip for use with carts and pallet trucks.

- **Easy:** to position thanks to the movable aluminum tongue.
- **Robust:** and lightweight, ideal for loads up to 1000 kg.
- **Versatile:** suitable for logistics, removals, events, and warehouses.

FAQ:

1. **Is the ramp suitable for manual pallet trucks?**
   Yes, it is designed for use with pallet trucks and carts with rubber wheels.
2. **Does the ramp have edges?**
   Yes, the ramp is equipped with edges.
3. **How does the anchoring tongue work?**
   The aluminum tongue slides and rotates in the ramp head for simple and secure fastening.
4. **Is installation required?**
   No, the ramp is ready for use. Simply position it and fix it using the tongues.
5. **Does it support heavy loads?**
   Yes, it has a capacity of up to 1000 kg at 1000 mm wheelbase, perfect for intensive use.

Mini buying guide:

Choosing a **professional loading ramp** means ensuring safety and operational continuity during handling phases.

The **H1026_01 model with edges** is perfect for environments where **pallet trucks or hand trucks** are used, thanks to the **non-slip surface**, **solid structure**, and **containment edges**.

The **movable tongues** simplify fastening to the support surface, making this ramp **versatile, safe, and ready for use**.

Excellent for those operating in **logistics, transport, events, or distribution**.

H1026_01 loading ramp with edges, non-slip ramp for pallet trucks, logistics ramp for hand trucks, ramp with anchoring tongue, removals and goods handling ramp.

**Images for illustrative purposes only.*

INFORMATION

- **Load capacity** 1000 Kg
- **Side edges** With edges

Loading ramp with edges h1026_01





Loading ramp with edges h1026_01

Flow rate: 1000 Kg
Side edges: With edges

