Namiti S.r.l. - P. Iva 06162571217 - N. Rea: 799272
Sede leg.: Via Cortile, 16 - 80069 Vico Equense (NA)
Sede Op.: Corso Italia, 192 - 80063 Piano di Sorrento (NA)
Email: vendite@holity.com / Tel. 0818087452



Loading ramp without edges h1026_02

Non-slip ramp for trolleys and pallet trucks. Length: 179.1 cm. Profile height: 6.5 cm. Capacity: 1000 kg.

The **H1026_02 loading ramp**, without side edges, is designed to facilitate **manual loading and unloading** operations in **logistics, industrial, exhibition and commercial** environments. It is a device particularly suitable for use with **manual pallet trucks, hand trolleys** or **equipment equipped with rubber wheels**, thanks to its **non-slip walking surface** which ensures optimal traction and maximum safety during use.

This platform is built with robust and lightweight materials and is capable of **supporting a load up to 1000 kg at 1000 mm wheelbase**, making it ideal for frequent and continuous use even in demanding operating conditions, such as in the **logistics, beverage delivery, moving or event setup** sectors.

It is equipped with an **aluminum anchoring tongue**, designed to **slide along the width of the ramp and rotate inside the head**. This allows for quick and safe adjustment of the tongue position for **stable anchoring to the supporting surface**. To complete the equipment, **closing caps for the head** are included, which prevent the tongue from accidentally coming out during use.

The **borderless** version guarantees maximum **freedom of movement** for the operator, facilitating operations on both sides of the platform.

Order the **H1026_02 loading ramp today!** Perfect for your logistics business, also available for multiple supplies or customizations.

Technical features:

- **Type:** loading ramp without edges
- **Walking surface:** non-slip
- **Capacity:** 1000 kg at 1000 mm wheelbase
- **Standard length (L):** 1791 mm
- **Internal width (A):** 690 mm
- **External width (B):** 750 mm
- **Profile height (D):** 65 mm
- **Unit weight:** 21 kg
- **Anchoring system:** mobile aluminum tongue
- **Equipment:** head closing caps included
- **Available variant:** also with edges (see model H1026_01)

Benefits for the user:

- **Ideal:** for hand trolleys and pallet trucks in intensive operational contexts.
- **Greater:** flexibility thanks to the absence of side edges.
- **System:** adjustable and safe anchoring with aluminum tongue.
- **Structure:** robust and lightweight for easy handling.
- **Perfect:** for logistics environments, events, warehouses and removals.

FAQ:

1. **Is this ramp suitable for manual pallet trucks?**
   Yes, it is specifically designed for pallet trucks and trolleys with rubber wheels.
2. **Is it also available with edges?**
   Yes, model H1026_01 is the version with side edges.
3. **How does the anchoring tongue work?**
   The aluminum tongue can slide horizontally and rotate in the head, for precise and safe anchoring.
4. **Is it ready for use?**
   Yes, it is supplied complete with the fixing tongue and head caps, ready for use.
5. **What is the maximum supported load?**
   Up to 1000 kg at 1000 mm wheelbase, ideal even for heavy loads.

Mini buying guide:

Choosing a **loading ramp without edges** is ideal for those who need **access on both sides** of the platform or for those working in confined spaces.

The **H1026_02** is a lightweight, safe and resistant solution, perfect for **logistics environments, temporary warehouses, trade fairs and events**.

The **anchoring system with mobile tongue** allows for rapid installation on different types of surfaces.

The **borderless structure** guarantees practical use and freedom of movement.

H1026_02 loading ramp without edges, logistics platform for pallet trucks, non-slip ramp for trolleys, ramp with anchoring tongue, ramp for loading and unloading goods.

**Images purely indicative.*

INFORMATION

- **Load capacity** 1000 Kg
- **Side edges** Borderless

Loading ramp without edges h1026_02





Loading ramp without edges h1026_02

Flow rate: 1000 Kg
Side edges: Borderless

