Namiti S.r.l. - P. Iva 06162571217 - N. Rea: 799272
Sede leg.: Via Cortile, 16 - 80069 Vico Equense (NA)
Sede Op.: Corso Italia, 192 - 80063 Piano di Sorrento (NA)
Email: vendite@holity.com / Tel. 0818087452

Safes for reception with digital electronic combination h7608

Safes for reception with digital electronic combination, with time-delayed opening programmable from 0 to 99 minutes.
Safes for reception h7608 with digital electronic combination with time-delayed opening programmable from 0 to 99 minutes.

Features:

- Thickness of front and door: 6 mm. Lasercut.
- Thickness of body: 2 mm.
- Lock controlled by a high performing electronic code provide by non volatile memory.
- Opening/closing with recessed handle and solenoid.
- Power supply 220 V. through transformer supplied with the safe or with 4 internal batteries 1,5 V. alkaline (not included)
- Emergency external power outlet with contacts directly on keyboard.
- High security lock with double-bitted key for emergency opening.
- Saw-resistant nickel-plated rotating bolts Ø 22 mm.
- Horizontal and top vertical bolts protected by drill resistant manganese steel plate 3 mm thick.
- Base and back fixing holes.
- Screw anchor bolts provided.
- Painting in epoxy powder.
- Slot mm 170x8 and chute.

INFORMATION

- **warranty** 2 anni
- **Altezza in millimetri** 280.0000
- **Larghezza in millimetri** 400.0000
- **Profondità in millimetri** 350.0000
- **Typology** in Mobile
- **opening type** Electronic combination
- **strengths** con feritoia antiripescaggio