



Operating room clock with keyboard h775_16

Wall clock for operating rooms. Operation: polarized pulse receiver. Dimensions: W.460 x D.45 x H.147 mm

Wall clock for operating rooms, equipped with a stainless steel case (IP65, IK03), crystal glass and keyboard. This device is capable of displaying hours, minutes and seconds, or it can be used as a stopwatch. **The characters have a height of 7 cm (5 cm for seconds), ensuring excellent readability up to a distance of 30 meters.**

Brightness is adjustable over four levels and the reading angle is 120°. The device can be silenced and programmed or set via two buttons. The digits are composed of 7-segment LEDs, each consisting of three LEDs. Power consumption is 55 mA.

The clock is designed to operate in a temperature range between -5°C and 55°C. **Power is supplied via 24V pulses.** Electrical protection is class 2 and PoE consumption is maximum 4W, class 0.

Clock technical specifications:

- Red LED digital clock
- Stainless steel casing (IP65, IK07) with mineral glass protection and keyboard compliant with operating room requirements.
- For indoor use
- Display of hours, minutes and seconds
- Character height: 7 cm (5 cm for seconds)
- Optimal reading distance: 30 meters
- Operation: 24V pulse receiver
- Recessed mounting with 4 holes
- Reading angle: 120°
- Silent operation
- Programming and setting via 2 buttons
- Digits consisting of 7 segments with 3 LEDs each
- Consumption: 55mA
- Operating temperature: from -5 to 55°C
- Weight: 2.2 kg
- Electrical protection: class 2
- Dimensions: W.460 x D.45 x H.147 mm

Keyboard technical specifications:

- Stopwatch hours - minutes - seconds from 0 to 23:59:59
- Waterproof with touch-sensitive keys
- Time display key with LED indicator
- Stopwatch function key with LED indicator
- Start/Stop key.
- Reset key: resets the stopwatch to zero.
- Connection to the clock via 2-wire telephone cable; maximum length 20 meters.
- Power supply via clock.
- Ability to manage up to 10 clocks.
- Operating temperature: from 0 to 50°C
- Protection rating: IP55
- Weight: 255g

Separately, as an **optional** extra, you can purchase the **recessed keyboard** and the **back cover**, useful for protecting the clock from dust and moisture.

**Other LED colors are available upon request for a quote*

***The clock requires a master controller (Master Clock/NTP server) to drive it via the relative output pulses*

INFORMATION

