



Operating room wall clock h775_07

Built-in operating room clock with keyboard. Dimensions: W.420 x D.45 x H.130 mm.

Professional operating room clock, made with red LED alphanumeric digits, **with a character height of 5 cm** and an optimal reading distance of 20 meters. The article also features a **stainless steel housing** (IP65, IK07) with mineral glass protection and a keyboard compliant with operating room requirements, and a **keyboard** that is connected to the clock via a 2-wire telephone cable. The operation of the item involves movement via **24 VV polarized pulse receiver and 110/230VAC power supply**.

Clock technical features:

- Red LED digital clock
- Stainless steel enclosure (IP65, IK07) with mineral glass protection and keyboard compliant with operating room requirements.
- For indoor use
- Hours, minutes and seconds display
- Character height: 5 cm
- Optimal reading distance: 20 meters
- Movement operation via 24 VV polarized pulse receiver and 110/230VAC power supply
- Built-in mounting with 4 holes
- Reading angle: 120°
- Silent operation
- Programming and configuration via 2 buttons
- Digits consisting of 7 segments with 3 LEDs each
- Consumption: 55mA
- Operating temperature: from -5 to 55°C
- Weight: 1.2 kg
- Electrical protection: class 2
- Dimensions: W.420 x D.45 x H.130 mm

Keyboard technical features:

- Stopwatch hours - minutes - seconds from 0 to 23:59:59
- Waterproof with touch-sensitive keys
- Time display key with LED indicator.
- Stopwatch function key with LED indicator.
- Start/Stop key.
- Reset key: resets the stopwatch to zero.
- Connection to the clock via 2-wire telephone cable; maximum length 20 meters.
- Powered via clock.
- Possibility to manage up to 10 clocks.
- Operating temperature: from 0 to 50°C
- Protection rating: IP55
- Weight: 255g

Separately, as an **optional**, it is possible to purchase the **built-in version of the keyboard** and the **back cover**, useful for protecting the clock from dust and moisture.

**Other LED colors are available upon request and quotation*

*** This clock requires a master regulator to drive it through the relative output pulses, available for purchase upon quotation*

INFORMATION

