



Pedestrian barrier steel with big advertising panel h14068

Barrier for urban ideal to mark the traffic in areas of high intensity pedestrian. With removable display panel edges and no sharp edges.

Barrier for urban ideal to mark the traffic in areas of high intensity pedestrian.

Structure:

- No. 02 pillars of support made of tubular galvanized steel mm. 60 x 2 complete with tappoterminale PVC spherical head;
- arches connecting galvanized iron plate mm. 50 x 10;
- display panel (removable) galvanized sheet metal and shaped 15/10 with bordiantitaglio at the top and bottom.

Pre-treatment:

- before being painted, the building is pre-treated by a spray wash degreasing conspeciali. After washing, the piece to be painted, is dried for 15 minutes in a dryer.

Anti-corrosion treatment:

- in order to impart suitable protection against atmospheric agents, the article is subjected to a first coating cycle using an anticorrosive primer in thermosetting powder epoxy diresine with special pigments.

Before kitchen (anticorrosive):

- the manufactured article treated with the anticorrosive primer is subjected to a first baking of duratadi 15 minutes at a temperature of 180 °. In this phase the anticorrosive polymerizes, forming unospessore of coating of about 60 microns.

Painting:

- , the product was subjected to a final cycle of painting with polyester thermosetting powder diresine color "gun barrel" (supporting struts). The paint is performed conapparecchiature electrostatic spray, which allow the powder to settle uniformementesui pieces, forming a minimum thickness of 60 microns.

Glaze firing:

- the coated manufacture is subjected to a final baking in the oven for a period of 20 minutes at a temperature of 160 °;
- spaces for posting unpainted.

Fixing:

- through the extension of the supporting struts in the subsurface.

Size:

Useful space posting:

- width cm. 93 - cm height short side. 50.

Hurdle:

- cm height above ground. 103;
- total width cm. 107;
- in-ground cm. 20;
- weight kg. 25.

INFORMATION