



Petrol transport tank h1042_10

Petrol transport tank h1042_10, 190 L capacity, made of black conductive LLDPE polyethylene, ADR approved (BAM 14341-CEMO6/500/273). Supplied assembled with orange lid, explosion-proof insert and 12V pump.

The **Petrol transport tank h1042_10** is a 190-liter mobile system approved for the safe road transport of highly flammable fuels, in full compliance with current ADR regulations (ADR Approval: BAM 14341-CEMO6/500/273). Made with a robust, high-quality uncoated black polyethylene (PE / LLDPE) tank, the material is electrically conductive to prevent risks from electrostatic charges and is internally equipped with a patented explosion-proof insert. The compact and easy-to-use structure is equipped with an orange hinged lid for additional protection of the transfer unit. The body integrates a dispensing nozzle holder to ensure order and cleanliness, a filling neck with integrated ventilation and vent for safe filling, forklift pockets, ergonomic handles, and structural recesses for secure fastening with ratchet straps during transport. Supplied in an already assembled condition, this container is subject to mandatory periodic inspection every 2.5 years according to ADR 6.5.4.4.1 b) and ADR 6.5.4.4.2 b). Dispensing is handled by a 12V DC electric pump with a maximum flow rate of 25 l/min, completed by a 4-meter flexible hose (DN 19), an automatic dispensing nozzle for petrol, and a 5-meter cable with battery pole clamps.

Technical features

- **Capacity:** 190 l
- **External dimensions (W x D x H):** 80 x 60 x 61 cm
- **Weight:** 39 kg
- **Use:** mobile
- **Place of use:** transport
- **Material:** LLDPE (high quality polyethylene)
- **Coating:** uncoated
- **Material properties:** electrically conductive
- **Active safety:** patented explosion-proof insert
- **Tank color:** black
- **Lid color:** orange
- **Lid:** yes (hinged)
- **ADR Approval:** BAM 14341-CEMO6/500/273
- **Legal inspections:** periodic control every 2.5 years according to ADR 6.5.4.4.1 b) and ADR 6.5.4.4.2 b)
- **Operating voltage:** 12V DC

- **Pump drive:** electric pump
- **Maximum flow rate:** 25 l/min max.
- **Delivery hose length:** 4 m
- **Hose diameter:** DN 19
- **Stackable:** yes
- **Forklift pockets:** yes
- **Dispensing nozzle:** automatic for petrol
- **Cable length:** 5 m
- **Plug / connection:** battery pole clamps
- **Compatible fluids:** Petrol
- **Assembly status:** assembled
- **Warranty in years:** 1

** Images are purely indicative*

INFORMATION

- **Adatto per Fuel**
- **Capacità 190 L**

Petrol transport tank h1042_10

: Fuel
: 190 L

