



Polyethylene diesel tank 440 lt h466_08

440L polyethylene tank for diesel h466_08 (1200x800 mm). Rotational molding, 12/24V pump, level indicator and automatic nozzle.

The **polyethylene diesel tank 440 lt h466_08** is a mobile tank developed for the safe transport and dispensing of fuel in operational contexts. Made of linear polyethylene through rotational molding, it offers a compact and lightweight structure that solves the problem of on-field refueling for vehicles and operating machines. Aimed at construction companies, agricultural businesses, and earthmoving professionals, the tank facilitates logistics thanks to the handles for empty lifting and the base design for use with forks when fully loaded. The system is complete with a dispensing unit with an FLK pump (powered by 12 or 24 volts), a 6-meter carbopress rubber hose, a level indicator, and an automatic shut-off nozzle, ensuring efficient transfer protected by a solid lid with a key lock.

Technical characteristics

- **Nominal capacity:** 440 liters
- **Dimensions (L x D x H):** 1200 x 800 x 800 mm
- **Empty weight (with pump unit):** 54 kg
- **Tank material:** Linear polyethylene with rotational molding
- **Structural components:** Brass inserts
- **Pump unit:** FLK 12 or 24 volt
- **Flow rate:** Approximately 35 lt/1'
- **Delivery hose:** In 3/4" carbopress rubber (6 mt length)
- **Nozzle:** Automatic shut-off
- **Power supply:** Battery connection cable with clamps (4 mt length)
- **Safety and control:** Protective cover with key lock, level indicator, filling cap with integrated vent
- **Handling:** Handles for empty lifting; setup for lifting and moving when full with forks
- **Certification:** CE

Optional:

- **Digital flow meter:** for low viscosity fluids with a turbine measurement system.

** Images are purely indicative*

INFORMATION

- **Adatto per Diesel**
- **Capacità 440 L**



Polyethylene diesel tank
440 lt h466_08

: Diesel
: 440 L