



Road gully with hinge h638_36

Flat road gully in ductile iron. External dimensions: 400 x 400 mm. Height: 75 mm.

The road gully is a fundamental urban furniture element to ensure **proper rainwater collection**, preventing it from accumulating on the road surface. At the same time, the product represents a **safety device** aimed at preventing cars and passers-by from suffering damage due to uneven road surfaces. The product features a **ductile iron structure** built **according to UNI EN 124 standards** and consists of a **square-shaped frame** at both the support base and the top corresponding to the road level, and a square grid.

The frame is equipped with:

- Continuous external perimeter flange on all four sides
- Reinforcing ribs
- Shaped lugs on the inner edge for locking the grid closing system
- Holes for grid articulation
- Internal flanges at the four corners for housing an optional siphon

The grid is equipped with:

- Parallel slots
- Closing system, unlockable with a generic lever
- Holes for articulation to the frame
- Pair of nuts and bolts inserted to prevent theft and tampering
- Anti-slip relief pattern

Technical features:

- Material: ductile iron UNI EN 124
- Siphonable
- Anti-theft locking
- Automatic closing
- Hinge
- External dimensions: 400 x 400 mm
- Clear opening: 300 x 300 mm
- Height: 75 mm
- Drainage dm²: 3.98
- Weight: 18.50 kg

INFORMATION

- Length in millimetres 400.000000
- Depth in millimetres 400.000000
- Height in millimetres 75.000000

