




Road gully with octagonal frame h638_148

Spheroidal graphite cast iron gully with octagonal frame and round cover. Class: D400. External dimensions: Ø 850 mm.

This **road gully** in **spheroidal graphite cast iron** according to **UNI EN 124 standard** is **ISO 9001:2015 certified**. Its structure consists of an **octagonal frame** at the support base and **circular at the top**, corresponding to the street level. The frame includes a **continuous external perimeter flange** equipped with **slots for foundation anchoring**; **internal rebate with noise-reducing and anti-rocking elastomer gasket**; **appropriately shaped lug** on the internal edge for locking the grate closing system; **eyelets** functional for handling during installation phases; **closed-bottom hinge compartment** with lid locking system in open position. The **circular-shaped grate** with **honeycomb slots** is equipped with a **closed-bottom slot** ideal for accommodating any lever for unlocking and opening; **automatic closing system** made with a tilting tongue, appropriately shaped, bolted to the lid and with a helical contrast spring subjected to compression; **non-slip reliefs**; and an **appendix** designed to ensure the articulation of the lid to the frame in the hinge compartment which does not compromise the removability of the lid itself.

Technical features:

- External dimensions: Ø 850 mm
- Height: 100 mm
- Net opening: Ø 610 mm
- Drainage: 9 dm²
- Total weight: 54 kg
- Material: spheroidal graphite cast iron
- Flat surface
- Frame shape: octagonal
- Cover shape: circular
- Automatic closure
- Hinge
- 90° hinge block
- Gasket
- Honeycomb grate
- Non-slip reliefs and identification detail of the external frame dimensions expressed in cm
- Class: D400
- Manufactured according to the UNI EN 124 standard
- ISO 9001:2015 certification

**Images are purely indicative*

INFORMATION

- Length in millimetres 850.000000
- Depth in millimetres 850.000000
- Height in millimetres 100.000000

