



Road gully with rectangular grating h638_153

Ductile iron road gully with non-slip relief. Class: KN400. External dimensions: 400 x 500 mm.

Road gully in ductile iron compliant with the **EN 1563** standard, with a breaking load exceeding **400 kN**, manufactured by an **ISO 9001:2015** certified company. Composed of a **rectangular frame** at both the base and the top, aligned with the road level. The gully is equipped with a **rectangular grating** featuring **parallel openings** arranged in two rows; a **30 mm central concavity** to ensure an ergonomic slope on the upper surface; a dedicated **central space** for the insertion of any lettering; and **anti-slip reliefs**. The product is ideal for **parking areas**, **car parks** and **road gutters**.

Technical features:

- External dimensions: 400 x 500 mm
- Height: 100 mm
- Clear opening: 330 x 430 mm
- Drainage: 5.89 dm²
- Total weight: 37 kg
- Material: ductile iron
- Frame shape: rectangular
- Frame without external perimeter flange
- Cover shape: rectangular
- Class: KN400
- Manufactured according to EN 1563
- ISO 9001:2015 certification
- Breaking load > 250 kN
- Space for potential customization
- Grating with high drainage capacity

**Images are purely indicative*

INFORMATION

- Length in millimetres 500.000000
- Depth in millimetres 400.000000
- Height in millimetres 100.000000

Road gully with rectangular grating h638_153

