



Road gully with square grating h638_150

Ductile iron gully with a square frame. Class: D400. External dimensions: 500 x 500 mm.

The **ductile iron gully** manufactured according to the latest edition of the **UNI EN 124** standard is ideal for rest areas, parking lots, and road gutters. Produced by an **ISO 9001:2015** certified company, this gully is designed to ensure quality and safety. Its structure consists of a **square frame** at both the base and the top, aligned with the road surface level. The product features a **square-shaped grating** with **parallel slots** arranged in two rows; a **30 mm central concavity** to facilitate the useful slope on the extrados; central space for **any lettering**; and **anti-slip reliefs** to guarantee user safety.

Technical features:

- External dimensions: 500 x 500 mm
- Height: 106 mm
- Clear opening: 450 x 450 mm
- Drainage area: 6.40 dm²
- Total weight: 43 kg
- Material: ductile iron
- Frame shape: square
- Cover shape: square
- Class: D400
- Manufactured according to the UNI EN 124 standard
- ISO 9001:2015 certification
- Breaking load exceeding 400 kN
- Space for possible customization
- Grating with high drainage capacity

**Images for illustrative purposes only*

INFORMATION

- Length in millimetres 500.000000
- Depth in millimetres 500.000000
- Height in millimetres 106.000000

Road gully with square grating h638_150

