



Road manhole cover with 3 covers h638_99

Ductile iron manhole cover with 3 square covers. Load class D400. Dimensions: 870x2365 mm.

Ductile iron manhole cover with three covers, produced by an ISO 9001:2015 certified company, according to the latest edition of the UNI EN 124 standard, **load class D400**, for use in areas accessible to cars and trucks, including road carriageways, hard shoulders, and pedestrian areas. Consisting of a **rectangular frame** at both the support base and the top corresponding to the road level, equipped with a suitable external perimeter flange, continuous on all four sides, **appropriately shaped** and rounded at the corners to obtain a larger support base and allow **better anchoring** to the foundation also through holes/slots useful for fixing with anchor bolts; double internal "U" seat with **noise-reducing and anti-rocking elastomer gasket**; closed-bottom compartments with threaded hole for fixing the covers using recessed hexagonal head bolts. **Removable** crossbar to allow the use of the maximum clear opening, made **with a ^ profile**, equipped with a double internal "U" seat with double noise-reducing and anti-rocking elastomer gasket. **Square covers** equipped with a double seal appropriately shaped to ensure **maximum airtightness**; external appendages on the sides appropriately perforated for housing the frame fixing bolts; space for inserting any lettering and/or logos (e.g. contracting authority + etc.); closed-bottom slots suitable for lifting keys; identifying detail of the external dimensions of the frame expressed in cm; non-slip surface patterns uniformly **distributed for the complete drainage of surface water**.

Technical features:

- Material: ductile iron
- Load class D400
- Breaking load

INFORMATION

- **Material manhole covers** ghisa
- **manhole_dimensions** 870 x 2365 mm



Road manhole cover with 3 covers h638_99

Manhole cover dimensions: 870 x 2365 mm

Manhole cover material: ghisa