



Road manhole cover with inspection hatch h638_86

Road manhole cover with inspection hatch. Class C250. Dimensions: 600x600 mm.

Ductile iron manhole cover manufactured according to the latest edition of **the UNI EN 124 standard, load class C250**, by an **ISO 9001:2015 certified** company, consisting of a **square-shaped** frame at both the support base and the top corresponding to the road level, equipped with an external perimeter flange appropriately shaped and smoothed at the corners to obtain a larger support base and allow **better anchoring to the foundation**; internal "U" seat to achieve odor-tightness by filling with sand and/or equivalent materials in coupling with the covers. **Double cover**, of which the central one is suitable for inspection, equipped with closed-bottom slots suitable for the lifting key; side through-bolt for lifting the central cover, space for inserting any text and/or logos (e.g. contracting authority + etc.); anti-slip patterns appropriately distributed for complete runoff water drainage.

Technical characteristics:

- Material: ductile iron
- Airtight
- Square cover
- Square frame
- External dimensions: 600x600 mm
- Clear opening: 500x500 mm
- Height: 55 mm
- Weight approx. 45 kg
- Inspection opening: 202x202 mm
- Breaking load > 250 kN
- Class: C250

*image for illustrative purposes only

INFORMATION

- **Material manhole covers** ghisa
- **manhole_dimensions** 600 x 600 mm



Road manhole cover with inspection hatch h638_86

Manhole cover dimensions: 600 x 600 mm

Manhole cover material: ghisa