



Tank with pump and hinged lid h1042_09

120 L tank with pump and hinged lid h1042_09 made of black conductive cross-linked polyethylene, ADR approved for Petrol (BAM 14341-CEMO/321/173). Supplied assembled with explosion-suppression insert and 12V pump.

The **Tank with pump and hinged lid h1042_09** is a 120-liter mobile system specifically developed and approved for the highly secure road transport of Petrol, in compliance with the strict provisions of ADR regulations (Ministerial approval BAM 14341-CEMO/321/173). Built with a robust tank in high-quality black cross-linked polyethylene (PE / LLDPE), the material is electrically conductive to prevent electrostatic build-up and is internally equipped with a patented insert for explosion suppression. The compact and easy-to-use structure features an orange hinged flip-up lid for additional protection of the dispensing components. The tank body integrates a nozzle holder, a filling neck with integrated aeration and vent for safe filling, forklift pockets, ergonomic handles, and structural recesses for stable fastening via ratchet straps during transport. Supplied in a fully assembled condition, the system is subject to periodic inspection every 2.5 years according to ADR points 6.5.4.4.1 b) and ADR 6.5.4.4.2 b), and features a 12V DC electric pump (maximum flow rate 25 l/min) with a 4-meter delivery hose (DN 19), an automatic dispensing nozzle for petrol, and a 5-meter electric cable with battery clips.

Technical features

- **Volume:** 120 l
- **External dimensions (L x W x H):** 80 x 60 x 47 cm
- **Weight:** 30.5 kg
- **Usage:** Mobile
- **Installation location:** Transport
- **Material:** High-quality cross-linked polyethylene (PE) / LLDPE
- **Coating:** Uncoated
- **Material properties:** Electrically conductive
- **Active safety:** Patented explosion-suppression insert
- **Tank color:** Black
- **Lid color:** Orange
- **Lid:** Yes (hinged / flip-up)
- **ADR approval:** BAM 14341-CEMO/321/173
- **Legal checks:** Mandatory periodic inspection every 2.5 years according to ADR 6.5.4.4.1 b) and ADR 6.5.4.4.2 b)
- **Operating voltage:** 12V DC
- **Pump drive:** Electric pump
- **Max flow rate:** 25 l/min max.
- **Delivery hose length:** 4 m
- **Hose diameter:** DN 19
- **Stackable:** Yes
- **Forklift pockets:** Yes
- **Dispensing nozzle:** Automatic for petrol
- **Cable length:** 5 m
- **Connector:** Battery clips
- **Suitable fluids:** Petrol
- **Assembly status:** Assembled
- **Warranty in years:** 1

* Images are purely indicative

- Adatto per Fuel
- Capacità 120 L

HOLITY.COM

Tank with pump and hinged lid h1042_09

Tank with pump
and hinged lid
h1042_09

: Fuel
: 120 L

