



Wooden playground cableway h350_313

Inclusive playground cableway consisting of 2 vertical posts, 1 steel cable and 1 wooden platform. Dimensions: L. 1330 x W. 110 x h. 324 cm.

Playground cableway made of **laminated Nordic pine wood** pressure-treated in an autoclave with non-toxic salts. The equipment is composed of n. **2 vertical posts** section 12x12 cm to be anchored to the ground at different heights and connected on the back to **two inclined tie rods**. These are made of hot-dip galvanized steel round tube with a diameter of 60 mm, oven-painted at 180°. There are n. **2 reinforcement modules** supporting the posts, consisting of wooden poles section 9x9 cm, pantographed phenolic-glued okoume mahogany plywood panels **without sharp edges** and **buttresses in galvanized and oven-painted steel tube at 180°**. On the starting module, there is a **platform** made of phenolic-glued birch plywood, finished with colored films on both sides. N. **1 sliding system on multi-strand galvanized steel cable**, including **elastic stop devices at the ends**. The **flat seat** has a circular shape and is made of shock-proof rubber with an internal core in press-bent steel sheet, suspended from a **welded and hot-dip galvanized close-link chain**. All elements are assembled using **8.8 galvanized steel bolts** and **self-locking nuts**. The wooden parts are treated with high-penetration, non-toxic, water-dilutable wax-based colored impregnating agent. **Colored nylon nut caps** and **hot-dip galvanized metal attachments for ground anchoring** are included. **Certified in compliance with European Standards EN 1176 by the German Institute TÜV - SÜD.**

Technical features:

- Dimensions: L. 1330 x W. 110 x h. 324 cm
- Impact area: 53.00 square meters
- Total weight: 25 kg
- Number of users: 1
- Minimum space: 1375 x 400 cm
- Fall height: 100 cm
- Age of use: 2 - 8 years
- Inclusive play
- EN 1176 Certified

**Images are purely indicative.*

INFORMATION